### **PLANT INFORMATION**

**PSA Ref #**: 00207 Model No: TC14R

Plant Name: TURF CUTTER TC14R

Manufacturer: Crommelins Machinery WA

Manufacturer's Website: www.crommelins.com.au

Web Link for Plant: www.crommelins.com.au Potential noise level in dB: 85 to less than 95

Required hearing protection class: 2

**Mandatory Personal Protective Equipment:** 









Protection

Protection

Clothina



## **RISK ASSESSMENT INFORMATION**

Operator	Competency	: Plant Licence	Not Required

#### Potential Hazard(s) Risk Level Control Measure(s)

Exposure to ultraviolet radiation

if working outdoors.

Medium

Explosion or fire from fuel

vapours.

Medium

Wear sunscreen, hat, long sleeves and long

THE CROMMELIN GROUP

 Stop the engine before refuelling. Do not refuel while hot. Avoid spillage of fuel when refuelling. Ensure the fuel cap is properly secured after refuelling. Carry out visual checks for fuel leaks and repair before operation. Keep flammables away from the engine. Read and understand the warning label on the engine. Do not smoke while operating, servicing or refuelling this machine. Use unleaded fuel only.

Inhaling exhaust or fuel fumes.

Medium/Low

 Only operate in a well ventilated area. Do not operate in a confined space. Avoid breathing petrol fumes. Avoid skin contact with petrol.

Friction due to coming into contact with hot parts of the engine.

Medium/Low

• The muffler is fitted with a heat shield. Let the engine cool down before attempting any maintenance. Avoid contact with hot components. Warning label on engine.

Ergonomics due to constrained body posture or the need for

Medium/Low

 Take regular breaks for postural relief and safe work practises.

excessive effort.

Issue #: 9 • Issued 15-5-2018 • Printed 15-5-2018 • Copyright ©2018 HRIA Ltd.

generated by the plant.

Cutting, stabbing, puncturing due Low to coming into contact with moving parts.

Noise due to excessive noise

Cut, stab, puncture due to Low coming into contact with the cutter blade.

Injury or ill health due to Low exposure to excessive vibration.

 Hearing protection with a rating of 10db must be worn.

- Belt guard fitted to plant. Do not remove guards or covers.
- Protective footwear must be worn at all times. Before commencing operation mark any submerged obstacles, sprinlers, etc.
   Keep hands abd feet well clear of the cutting blade.

 Keep hands and feet well clear of the cutting blade. Ensure that drive is disengaged and engine is turned off before attempting any adjustments or maintenance.

Protective footwear must be worn at all times.

 The operator needs to take regular breaks every hour or change activity to provide postural relief for safe work practises.

# Customer Identified Hazard(s)

## **Key Operating Instructions**

Before commencing operation mark any submerged obstacles, sprinklers, etc.

Low

To start, turn on the fuel tap by moving the lever to the down position.

Before starting ensure both the drive levers are disengaged.

Ensure the stop switch on the engine is in the ON position.

For cold starting close the choke lever.

Start the engine by pulling the recoil rope with the throttle in low speed position.

As the engine warms up return the choke lever to the open position.

Set the depth adjuster knob to the desired depth, increase the speed, engage the cutter lever and let the cutter cut under the turf. It may be easier to dig a start hole for the cutter blade.

The speed should be set to a comfortable walking pace.

To commence operation engage the drive lever to move forward.

To stop the machine disengage both the cutter and the drive lever, return the throttle to the idle position, turn the engine stop switch OFF and turn off the fuel tap.

Please refer to the User Guide and Operator's Manual for Operating Instructions

The Safety Information on this assessment has been developed for the Hire and Rental Industry to assist in the safe operation of this equipment.

This information contains general information only and should not be relied upon as a substitute for professional advice, which the user should seek before operating.

Once printed this is an uncontrolled copy.