

THE CROMMELIN GROUP







CHOOSING YOUR PUMP

Crommelins has a large range of pumps to meet all your pumping needs. From small portable pumps, fire fighting pumps, large capacity pumps to pumps for on-site construction and heavy duty pumping work.

STANDARD FEATURES

- Construction grade quality
- Low maintenance and long engine life
- Assembled and tested in Australia

PUMP TERMS

- **Total Head** The total height in meters liquid can be pumped to
- **Max. Suction** The maximum depth liquid can be sucked at below the level of the pump
- **Trash** Allows pumping in muddy/sandy water and will also pump solids
- Clean Water For clear water pumping only.
 Poly For pumping waste water, chemicals, sea water, etc.
- **Self Priming** Requires no water for subsequent pumping operation once initial pumping is done,and the pumping capacity is large.

CUSTOMISE YOUR PUMP

Crommelins can customise pumps to suit your needs.

OPTIONAL EXTRAS

- Long range fuel tank
- Mine specification
- Electric start
- Roll frame
- Fire extinguisher
- Safety stop
- Custom colouring



PRE-SEASON PUMP MAINTENANCE.

Before the bushfire season arrives or when you need to use your pump, it is wise to check your pump unit to make sure it is ready for service.

MAINTENANCE TIPS*

- 1. If not already done (at end of season) change the engine oil.
- 2. Drain any fuel left in the tank and fill with fresh petrol. Loosen the fuel bowl retaining bolt on carburettor and allow fresh fuel to flush through. Tighten the bolt.
- 3. Remove spark plug and put a couple of squirts or pour a little engine oil in the cylinder. Pull motor over three or four times. Remove plug and rinse in petrol and replace.
- 4. Fill pump unit with water and start pump in normal fashion. The engine can be run for 1-2 minutes without connecting to water tank as long as the pump is full of water.


If the motor does not start or run properly (lack of compression/blocked carburettor) it will be necessary to have the unit checked by your local service agent.

*Note: Service should be done in a workshop (clean area), not an open field.


PUMP CURVES

FIRE FIGHTING


PETROL CLEAR WATER & POLY




DIESEL CLEAR WATER



ELECTRIC SUBMERSIBLE



TRASH & FLEX. SUBMERSIBLE



CROMMELINS PETROL FIRE FIGHTING PUMPS.

These Fire Fighting pumps are known for their reliability, durability and versatility. They are ideal for fire fighting, water transfer, washing down farm machinery and many other jobs that require water at pressure. They come in either single or twin impeller.

STANDARD FEATURES

- 1 ¹/₂" Inlet (40mm)
- 1 ¹/₂" Outlet and 2 x 1" Outlet
- Cast aluminium impeller
- Bolt on replaceable suction port
- Cast iron diffuser increases pump life
- Cast aluminium pump body
- Metal (not plastic) delivery outlet caps
- 2 Years manufacturer's warranty
- Assembled and tested in Australia

IDEAL FOR

- Fire fighting
- Water transfer
- Washing down farm machinery
- Agriculture and farms
- Shires and councils

OPTIONAL EXTRAS

- Electric start
- Trolley kit
- Honda powered
- 2" Inlet / Outlets
- Hose kits available
- Viton seals

5	-
2	1.00
	100







	2 Aller	2	and the second	
	FF150RP/ 150HPROHC	FF150RP7 / 150HPROHC21	FT150RP / 150HPROHCT	FT150RP7 / 150HPROHCT21
WATER FLOW (L/MIN)	360L	420L	300L	360L
WATER FLOW (L/HR)	21,600L	25,200L	18,000L	21,600L
TOTAL HEAD (M)	60M	60M	90M	90M
MAX. SUCTION (M)	8M	8M	8M	8M
IMPELLER	SINGLE	SINGLE	TWIN	TWIN
ENGINE MODEL	6HP EX17	7HP EX21	6HP EX17	7HP EX21
ENGINE BRAND	ROBIN	ROBIN	ROBIN	ROBIN
FUEL TANK	3.6L	3.6L	3.6L	3.6L
DECIBELS @ 7M	66db	68db	66db	68db
WEIGHT (DRY)	24KG	25KG	30KG	32KG
DIMENSIONS (LxWxH)	510 x 440 x 440MM	510 x 440 x 440MM	510 x 440 x 440MM	510 x 440 x 440MM
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS	2 YEARS

CROMMELINS DIESEL FIRE FIGHTING PUMP.

These Fire Fighting pumps are known for their reliability, durability and versatility. They are ideal for firefighting, water transfer, washing down farm machinery and many other jobs that require water at pressure. They come in either single or twin impeller.

STANDARD FEATURES:

- 1 ¹/₂" Inlet (40mm)
- 1¹/₂" Outlet and 2 x 1" Outlet
- Cast aluminium impeller
- Bolt on replaceable suction port
- Cast iron diffuser increases pump life
- Cast aluminium pump body
- Metal (not plastic) delivery outlet caps
- 2 Years manufacturer's warranty
- Assembled and tested in Australia

IDEAL FOR

- Fire fighting
- Water transfer
- Washing down farm machinery
- Agriculture and farms
- Shires and councils



	150HPRDS
WATER FLOW (L/MIN)	300L
WATER FLOW (L/HR)	18,000L
TOTAL HEAD (M)	57M
MAX. SUCTION (M)	8M
IMPELLER	SINGLE
STARTING SYSTEM	ELECTRIC START
ENGINE MODEL	4.7HP L48
ENGINE BRAND	YANMAR
FUEL TANK	2.4L
DECIBELS @ 7M	94db @ 1M
WEIGHT (DRY)	51KG
DIMENSIONS (LxWxH)	530 x 420 x 490MM
MANUFACTURER'S WARRANTY	2 YEARS

OPTIONAL EXTRAS

- Electric start
- Mine specification
- 2" Inlet / Outlets
- Hose kits available
- Viton seals





CROMMELINS PETROL CLEAR WATER PUMPS.

These are ideal for general purpose pumping, for transfer of large volumes of water such as from a dam to a water tank. They are also popular on water trucks for spray bars and tree watering operations.

STANDARD FEATURES

- Genuine Robin engine
- Direct coupled pump ensures efficient, economical operation
- Self-priming pump requires no water for subsequent pumping operation once initial pumping is done and the pumping capacity is large
- Water-resisting qualities with mechanical seal made of ceramic-carbon and the impellers made of cast iron
- Cast alluminium impeller and inner casing
- 2 Years manufacturer's warranty

IDEAL FOR

- Hire and rental
- General purpose ater transfer
- Agricultural

OPTIONAL EXTRAS

• Electric start with AGM battery

	CP200RP / PTX201	CP300RP / PTX301	CP400RP / PTX401
INLET (IN)	2"	3"	4"
OUTLET (IN)	2"	3"	4"
WATER FLOW (L/MIN)	520L	1000L	1800L
WATER FLOW (L/HR)	31,200L	60,000L	108,000L
TOTAL HEAD (M)	32M	32M	28M
MAX. SUCTION (M)	8M	8M	8M
STARTING SYSTEM	RECOIL START	RECOIL START	RECOIL START
ENGINE MODEL	4.5HP EX13	6HP EX17	9HP EX27
ENGINE BRAND	ROBIN	ROBIN	ROBIN
FUEL TANK	2.7L	3.6L	6.1L
DECIBELS @ 7M	64db	66db	70db
WEIGHT (DRY)	25KG	28KG	45KG
DIMENSIONS (LxWxH)	470 x 344 x 414MM	527 x 368 x 417MM	610 x 425 x 565MM
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS



CROMMELINS DIESEL CLEAR WATER PUMPS.

These are ideal for general purpose pumping, for transfer of large volumes of water such as from a dam to a water tank. They are also popular on water trucks for spray bars and tree watering operations.

STANDARD FEATURES

- Genuine Yanmar diesel engine
- Direct coupled pump ensures efficient, economical operation
- Self-priming pump requires no water for subsequent pumping operation once initial pumping is done and the pumping capacity is large
- Water-resisting qualities with mechanical seal made of ceramic-carbon and the impellers made of cast iron
- Cast alluminium impeller and inner casing
- 2 Years manufacturer's warranty

IDEAL FOR

- Hire and rental
- General purpose ater transfer
- Agricultural

OPTIONAL EXTRAS

• Electric start with AGM battery

	РНОТО	ното	РИОТО	
	CP200YD WITH ROBIN ENGINE	CP300YDE WITH ROBIN ENGINE	CP400YDE WITH ROBIN ENGINE	
INLET (IN)	2"	3"	4"	
OUTLET (IN)	2"	3"	4"	
WATER FLOW (L/MIN)	520L	900L	1800L	
WATER FLOW (L/HR)	31,200L	54,000L	108,000L	
TOTAL HEAD (M)	32M	28M	25M	
MAX. SUCTION (M)	8M	8M	8M	
STARTING SYSTEM	RECOIL START	ELECTRIC START	ELECTRIC START	
ENGINE MODEL	4.7HP L48N	6.7HP L70	6.7HP L70	
ENGINE BRAND	YANMAR	YANMAR	YANMAR	
FUEL TANK	2.4L	3.3L	3.3L	
DECIBELS @ 1M	94db @ 1M	-	-	
WEIGHT (DRY)	41KG	44KG	100KG	
DIMENSIONS (LxWxH)	540 x 370 x 460	590 x 410 x 510	850 x 510 x 650	
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS	



CROMTECH PETROL CLEAR WATER PUMPS.

1" PORTABLE PUMP

This 4-stroke, compact, lightweight pump is for water transferring to dams, water tanks and more.

STANDARD FEATURES


- 25mm inlet and outlet
- Mechanical seal (ceramic carbon)
- Petrol powered
- Recoil start
- Transport handle
- Light weight
- 1 Year Cromtech warranty

IDEAL FOR

- Water transfer
- Emptying ponds, dams and large water tanks
- Agricultural and general purpose

ACCESSORIES

- 5m Suction hose included
- Tool kit
- Plastic funnel
- Hose-tails and strainer



CIPIOI
ך"
ך"
117L
7020L
30M
8M
RECOIL START
4-STROKE
CROMTECH
0.65L
7.0KG
380 x 300 x 380MM
1 YEAR

3" PUMP

This model comes with a 2" reducer to turn it into a higher-pressure water pump. The pump is compact and perfect for general use because of its multiple applications.


MODELS COMING IN 2019

STANDARD FEATURES

- 3" to 2" Reducer (Inlet/Outlet)
- Mechanical seal (ceramic carbon)
- Petrol powered
- Recoil start
- Steel frame protects model
- 1 Year Cromtech warranty

IDEAL FOR

- Water transfer
- Emptying ponds, dams and large water tanks
- Agricultural and general purpose



СТР301

	CIPSUI
INLET (IN)	3"
OUTLET (IN)	3"
WATER FLOW (L/MIN)	900L
WATER FLOW (L/HR)	54,000L
TOTAL HEAD (M)	30M
MAX. SUCTION (M)	7M
STARTING SYSTEM	RECOIL START
ENGINE TYPE	4-STROKE, 4.5KW
ENGINE BRAND	CROMTECH
FUEL TANK	2.6L
WEIGHT (DRY)	26KG
DIMENSIONS (LxWxH)	530 x 415 x 445MM
MANUFACTURER'S WARRANTY	1 YEAR

CROMMELINS POLY PUMPS.

The Crommelins Poly Pumps are durable and reliable pumps for applications where chemicals, waste water, salt water and mild caustic liquids have to be pumped. Constructed of corrosion-resistant materials it comes with 316 stainless steel fasteners throughout and viton seals.

STANDARD FEATURES

- Viton seals for pumping chemical liquids
- Corrosion resistant poly pump
- Heavy duty roll frame
- 2 Years manufacturer's warranty
- Assembled and tested in Australia

IDEAL FOR

- Chemicals and mild caustic liquids
- Waste water
- Salt water
- Flexi and fertiliser

OPTIONAL EXTRAS

- Genuine Robin industrial engine
- Electric start with AGM battery
- Yanmar diesel powered



	PP200HPV / 200PHV	PP300HPV / 300PHV	PP200YDEV / 200PYD	PP300YDEV / 300PYDE
INLET (IN)	2"	3"	2"	3"
OUTLET (IN)	2"	3"	2"	3"
WATER FLOW (L/MIN)	730L	1059L	7.30L	1059L
WATER FLOW (L/HR)	43,800L	63,540L	43,800L	63,540L
TOTAL HEAD (M)	38M	25M	38M	25M
MAX. SUCTION (M)	8M	8M	8M	8M
STARTING SYSTEM	RECOIL START	RECOIL START	RECOIL START	ELECTRIC START
ENGINE MODEL	GX200	GX200	4.7HP L48N	4.7HP L48
ENGINE BRAND	HONDA	HONDA	YANMAR	YANMAR
FUEL TYPE	PETROL	PETROL	DIESEL	DIESEL
FUEL TANK	3.1L	3.1L	2.4L	2.4L
DECIBELS @ 7M	N/A	N/A	94db @ 1M	94db @ 1M
WEIGHT (DRY)	28KG	38KG	50KG	63KG
DIMENSIONS (LxWxH)	530 x 420 x 490MM	730 X 485 X 610MM	530 X 420 X490MM	730 X 485 X 610MM
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS	2 YEARS

CROMMELINS PETROL TRASH PUMPS.

Trash pumps handle larger solids and debris for heavy-duty de-watering applications. A trash pump uses deep impeller vanes with a large volute and pumps water containing suspended sticks, stones & debris without clogging or harming pump components.

STANDARD FEATURES

- Genuine Robin/Honda petrol engine
- Self-priming with no water required after initial priming is done.
- Silicon-carbon mechanical seal
- Cast iron impeller and inner casing
- Quick clean-out suction port provides easy maintenance and long service life.
- 2 Years manufacturer's warranty
- Assembled and tested in Australia

IDEAL FOR

- Rental and hire •
- General purpose de-watering •
- Construction job site •
- Agricultural •

OPTIONAL EXTRAS

- Electric start with AGM battery
- Honda powered

PUMP CURVE: REFER TO PAGE 54

	a de la competition de la comp	T.		
	TP200RP / PTX201T	TP300RP / PTX301T	TP400RP / PTX401T	
INLET (IN)	2"	"3	4"	
OUTLET (IN)	2"	3"	4"	
WATER FLOW (L/MIN)	750L	1300L	2000L	
WATER FLOW (L/HR)	45,000L	78,000L	120,000L	
TOTAL HEAD (M)	27M	28M	23M	
MAX. SUCTION (M)	8M	8M	8M	
STARTING SYSTEM	RECOIL START	RECOIL START	RECOIL START	
ENGINE MODEL	6HP EX17	9HP EX27	12HP EX35	
ENGINE BRAND	ROBIN	ROBIN	ROBIN	
FUEL TANK	3.6L	6.1L	7.0L	
DECIBELS @ 7M	66db	69.5db	74db	
WEIGHT (DRY)	35KG	49KG	72KG	
DIMENSIONS (LxWxH)	570 x 436 x 397MM	672 x 484 x 610MM	730 x 485 x 600MM	
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS	



Anna





CROMMELINS DIESEL TRASH PUMPS.

Trash pumps handle larger solids and debris for heavy-duty de-watering applications. A trash pump uses deep impeller vanes with a large volute and pumps water containing suspended sticks, stones & debris without clogging or harming pump components.

STANDARD FEATURES

- Genuine Yanmar diesel engine
- Self-priming with no water required after initial priming is done.
- Silicon-carbon mechanical seal
- Cast iron impeller and inner casing
- Quick clean-out suction port provides easy maintenance and long service life.
- 2 Years manufacturer's warranty
- Assembled and tested in Australia

IDEAL FOR

- Rental and hire
- General purpose de-watering
- Construction job site
- Mining and oil

OPTIONAL EXTRAS

- Electric start with AGM battery
- Mine specification

	PHOTO WITH ROBIN ENGINE	PHOTO	PHOTO WITH ROBIN ENCINE
	TP200YD / PTG205TYD	TP300YDE / PTG305TYDE	TP400YDE / PTG405TYDE
INLET (IN)	2"	3"	4"
OUTLET (IN)	2"	3"	4"
WATER FLOW (L/MIN)	680L	1170L	2000L
WATER FLOW (L/HR)	40,800L	70,200L	120,000L
TOTAL HEAD (M)	24M	25M	21M
MAX. SUCTION (M)	8M	8M	8M
STARTING SYSTEM	RECOIL START	ELECTRIC START	ELECTRIC START
ENGINE MODEL	4.7HP L48N	4.7HP L48	10.0HP L100
ENGINE BRAND	YANMAR	YANMAR	YANMAR
FUEL TANK	2.4L	2.4L	5.4L
DECIBELS @ 7M	94db @ 1M	94db @ 1M	97db @ 1M
WEIGHT (DRY)	55KG	100KG	95KG
DIMENSIONS (LxWxH)	590 x 510 x 550MM	850 x 510 x 650MM	-
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS



CROMTECH SUBMERSIBLE PUMPS.

Constructed with stainless steel and cast iron, there is a pump to suit most applications. These pumps are ideal for pumping grey and clean water out of water tanks, pools, ponds, sewage and flooded areas.





OPTIONAL EXTRAS

- Available without float switch (except 750F)
- Hose kits available

STANDARD FEATURES

- Float switch (F) automatically turns pump on/off
- High quality bearing, seals
- Stainless motor shaft
- Single phase electric motor
- Overload protection
- 7m rope to lower/lift pump
- 10m long power cord
- Vortex impeller

IDEAL FOR

- Pools and ponds
- Flooded areas
- Sewage
- Dewatering











		. · · · · ·		State - state	and the second se	
	MQ350LINOX	V180F	V250F	V450F	V750F	V1100DF
OUTLET (MM)	25/32MM	25/32MM	25/32/40MM	50MM	50MM	50MM
WATER FLOW (L/MIN)	108L	133L	150L	200L	300L	233L
WATER FLOW (L/HR)	6480L	7980L	9000L	12,000L	18,000L	13,980L
TOTAL HEAD (M)	6M	7M	7.5M	8.5M	10.5M	7M
MAX. SOLIDS (MM)	3MM	15MM	15MM	25MM	25MM	25MM
IMPELLER	OPEN VANE VORTEX	OPEN VANE VORTEX/ PRE- CHOPPER BLADE				
MOTOR	350W	180W	250W	450W	750W	1100W
WEIGHT (DRY)	5KG	8.5KG	9KG	17KG	21KG	23KG
DIMENSIONS (LxWxH)	-	200x190x390MM	200x190x400MM	270x200x520MM	270x207x560MM	275x225x560MM
MANUFACTURER'S WARRANTY	1 YEAR	1 YEAR				

CROMTECH SUBMERSIBLE PUDDLE PUMP.

When you have those nuisance puddles or flooding on site and conventional pumps don't drain low enough, the Cromtech Puddle Pump is the answer. This pump will operate on most surfaces down to Imm leaving the bare minimum of water.

STANDARD FEATURES

- Adjustable discharge outlet
- Operates on most surfaces
- Drains down to 1mm water level
- Single phase electric motor
- Overload protection
- 10m long power cord
- Vortex impeller

IDEAL FOR

- Rental and hire
- General purpose de-watering
- Construction sites
- Slabs and footings
- Agriculture
- Pools and ponds
- Flooded areas
- Versatile for all industries



	CPP450
OUTLET (MM)	25MM
WATER FLOW (L/MIN)	85L
WATER FLOW (L/HR)	5100L
TOTAL HEAD (M)	10M
MAX. SOLIDS (MM)	0.2MM
IMPELLER	OPEN VANE VORTEX CAN PUMP DOWN TO 1MM WATER LEVEL
MOTOR	450W
WEIGHT (DRY)	12KG
PACKAGE DIMENSIONS (LxWxH)	230 x 230 x 350mm
MANUFACTURER'S WARRANTY	1 YEAR



CROMTECH





PUMPS



CROMMELINS FLEXIBLE SUB. PUMPS.

These 50mm pumps are heavy duty and designed to handle the toughest of jobs. The submersible pump attaches to the drive units for rapid removal of water containing solids in footings, manholes, tanks, drainage, emptying pools, waste transfer and much more.

STANDARD FEATURES

- Cast Iron or aluminium pump casing
- Wide suction passages to allow debris (up to 25mm) to pass through
- Can allow fluids containing up to 60% solids
- Quick action flexshaft coupling with 3 dog drive
- Includes adaptor for cam lock/discharge hose
- 6m length
- Rope included to lift the pump in/out of holes
- Movable spiral section to prevent kinking
- 1 Year manufacturer's warranty

OPTIONAL EXTRAS

- 3M Extension shaft
- 6M Extension shaft
- Drive units
- Hose kits available



	FP2T
OUTLET (IN)	2" (50MM)
WATER FLOW (L/MIN)	933L
WATER FLOW (L/HR)	56,000L
TOTAL HEAD (M)	29M
PUMP TYPE	CAST IRON
MAX. SOLIDS (MM)	25MM
IMPELLER	OPEN VANE
DRIVE TYPE	3 DOG
WEIGHT (DRY)	33KG
DIMENSIONS PACKAGE (LxWxH)	1000 x 770 x 200MM
MANUFACTURER'S WARRANTY	1 YEAR



IDEAL FOR

- Rental and hire
- Manholes
- Drainage





	FP2TA
OUTLET (IN)	2" (50MM)
WATER FLOW (L/MIN)	933L
WATER FLOW (L/HR)	56,000L
TOTAL HEAD (M)	29M
ΡυΜΡ ΤΥΡΕ	ALUMINIUM
MAX. SOLIDS (MM)	25MM
IMPELLER	OPEN VANE
DRIVE TYPE	3 DOG
WEIGHT (DRY)	32KG
DIMENSIONS PACKAGE (LxWxH)	1000 x 770 x 200MM
MANUFACTURER'S WARRANTY	1 YEAR

CROMMELINS SKID MOUNT WATER CART.

Built to order, Crommelins Water Cart is designed to be easily placed onto to a 6x4 or 8x5 trailer or Ute tray. There is three models to choose from nd each include a 6.0hp Crommelins Fire Fight Pump as standard.

STANDARD FEATURES

- Crommelins FF Pump [FF150RP]
- 30m, ¾" hose on hose reel
- Adjustable spray nozzle
- Recirculation hose with bypass valve back to tank
- 6m Suction hose with valve for filling from dam.
- Hot dipped galvanized steel skid (square tube)
- Base with lifting points
- 1 Year manufacturer's warranty



IDEAL FOR

- Rental and hire
- General purpose watering
- Construction and Civil Works
- Agriculture

OPTIONAL EXTRAS

- Twin impeller pumps
- Honda powered
- Yanmar diesel powered
- Forklift pockets
- Customisation to suit customer needs







	FS600RP / 600LTFFP	FS800RP / 800LTFFP	FS1000RP / 1000LTFFP
WATER TANK CAPACITY	600L	800L	1000L
SKID MOUNT FEATURES	FITS STANDARD 6X4 TRAILER (LOAD CAPACITY 745KG)	FITS STANDARD 6X4 TRAILER (LOAD CAPACITY 945KG)	FITS STANDARD 8X5 TRAILER (LOAD CAPACITY 1165KG)
WATER FLOW (L/MIN)	360L	360L	360L
WATER FLOW (L/HR)	21,600L	21,600L	21,600L
TOTAL HEAD (M)	60M	60M	60M
MAX. SUCTION (M)	8M	8M	8M
IMPELLER	SINGLE	SINGLE	SINGLE
STARTING SYSTEM	RECOIL START	RECOIL START	RECOIL START
ENGINE MODEL	6HP EX17	6HP EX17	6HP EX17
ENGINE BRAND	ROBIN	ROBIN	ROBIN
FUEL TANK	3.6L	3.6L	3.6L
DECIBELS @ 7M	66db	66db	66db
WEIGHT (DRY)	145KG	145KG	160KG
WEIGHT (WET)	745.G	945KG	1165KG
DIMENSIONS (LxWxH)	1170 x 1180 x 1000MM	1170 x 1180 x 1000MM	1760 x 1500 x 1000MM
MANUFACTURER'S WARRANTY	2 YEARS	2 YEARS	2 YEARS



WARRANTY





3 YEAR ROBIN ENGINE WARRANTY

Robin Industrial Engines and Robin Imported Products (Pumps, Generators) come with a 3 year manufacturer's warranty.



2 YEAR MANUFACTURER'S WARRANTY

CROMMELINS™ brand products powered by a Robin Industrial Engine come with a 2 year manufacturer's warranty.



1 YEAR MANUFACTURER'S WARRANTY

All other products including CROMMELINS[™], CROMTECH[™], flexible drive products (ie FP2T), high pressure pumps and imported products come with a 1 year manufacturer's warranty.



OTHER BRANDS WARRANTY

Other branded products come with warranties provided by their manufacturer, ie. Golz, American Sanders, AR Blue Clean.

AWARD WINNING SERVICE & BACKUP

PAGE || 111

WARRANTY EXPLAINED

Crommelins Machinery warrants their goods against defects in materials and workmanship under normal use and service.

The Crommelins Machinery warranty does not cover fair wear commensurate with the age of the product, any damage caused by accident, abuse, misuse, neglect or failure to observe proper operating instructions or proper machinery maintenance as described in the instruction manual.

It is the owners responsibility to regularly maintain a product in accordance with the owners manual and only use the equipment for its designed purpose.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

CONSUMER ADVICE

Any claim under these warranties must be made within warranty period from the date of purchase of the product.

To make a claim under the warranty, you must return the product (with proof of purchase) to the closest warranty agent or to the place of purchase.

Where a failure does not amount to a major failure, Crommelins Machinery is entitled to choose between providing you with a repair, replacement or refund. To obtain compensation, you would need to provide documentary evidence of the loss or damage suffered, and documentary evidence that such loss or damage was a reasonably foreseeable consequence of a failure by Crommelins Machinery to comply with a consumer guarantee under the Australian Consumer Law. CROMMELINS[™], CROMTECH[™], CROMTECH OUTBACK[™], CROMMELINS FINANCE[™], DOLPHIN[™] is registered trademarks of Crommelins Operations Pty Ltd, trading as The Crommelin Group.

SERVICE AGENTS

There are over 185 national authorised service/repair agents available, visit www.crommelins.com.au for their details and locations. For engine brands other than Robin please contact the manufacturer for service agents.

CROMMELINS PRODUCTS

Crommelins takes pride in all products they sell and they live by their company Mission Statement; "To be the supplier of choice to Hire and Construction Industry by providing high quality portable powered products."

THE CROMMELIN GROUP

	ABN 11 008 889 656
	PO Box 352, BENTLEY WA 6982
PH	(08) 9350 5588
FAX	(08) 9451 6381
Е	email@crommelins.com.au







EDITION 2 - NOV 2018